


SPARKLIFT

RENOVATOR FOR GELCOAT AND PAINT P.T.F.E. BASED



SPARKLIFT is a renovator containing P.T.F.E. The P.T.F.E. is a resin, which has a very low coefficient of friction.

The application on the hull of a film of P.T.F.E makes it possible to decrease the friction and the wear and tear on the gelcoat and paint.

The P.T.F.E makes it possible to reduce the matter loss due to the demonstrations of friction of water, salt, oxygen on the gelcoat or paint.

The renovating SPARKLIFT thus acts as insoluble, inert and anti-wear solid lubricant.

SPARKLIFT is a surface treatment containing P.T.F.E which leaves a brilliant film.

The application can be done only using one grinder orbital grinding machine.

Work on a speed of 300-500 tours minutes.

Work on small surfaces of 50/50 cm.

Spread the product equally on the bonnet, a coffee spoon is enough.

Move the grinding machine in circular motions at a low speed.

With the release of heat caused by this friction, the P.T.F.E. will be polymerized and migrate consequently in the middle of gelcoat.

Finish glossing by using a soft felt to obtain a perfect brightness.

Ref. 612M - Bottle 500 ml
Shelf Life : 2 years

IMPORTANT : Keep out of reach of children. In the event of contact with eyes, rinse immediately and abundantly with clear water at least 15 minutes. If irritations persist, consult a doctor. Always make beforehand, a test with the surface to be treated to determine the compatibility and the time of contact suited

This document does not imply our responsibility as to specific applications. Matt Chem Marine® is a registered-mark by Matt Chem Product®.



SAS MATT CHEM PRODUCT®
FRENCH MANUFACTURE
(92) Bagneux France
Tel : (33) 1 42 53 73 73 – Fax : (33) 1 47 35 27 28
www.matchem.com - info@matchem.fr
November 2011