

## **Technical Data Sheet**

Effective: 31/07/2019 Supersedes: 07/08/2007

### **Automotive Aftermarket Division**

# 3M<sup>™</sup> 55535 Finish Control Spray

#### 1) Part Numbers

55535

#### 2) Description and end uses

3M<sup>™</sup> Finish Control Spray is the ideal product to check the progress in any finishing operation, particularly to see if micro scratches from previous sanding steps are as polished out as they should be.

It is specially designed and tested to be compatible with all cured refinish paint systems, leaving any surface clean and ready for inspection.

Particularly recommended to always use after the first compounding step.

#### Product highlights:

- Reliably removes any compound residue
- Reduces the risk of undetected micro scratches coming back
- Helps to achieve the perfect finish result
- Also suitable for a quick surface clean, leaving no streaks

#### 3) Physical Properties

Base	:	Water-based
Colour	:	White
Consistency	:	Foam
Solvent	:	Water
Propellant	:	Hydrocarbon
VOC	:	50g
Application	:	+15°C to
temperature		+30°C



## **Technical Data Sheet**

Effective: 31/07/2019 Supersedes: 07/08/2007

#### 4) Directions for Use

- Wait until compounded/polished area has cooled off
- Shake can before use
- Apply a liberal amount of Control Spray from a distance of 20 30 cm to surface
- Wipe off with a high-performance wipe (i.e. 34568 3M<sup>™</sup> Disposable Polishing Wipe or 50400 Polishing Wipe)
- Control for residual sanding scratches. If these scratches are still visible, repeat previous compound step

CAUTION: Do not apply to hot surfaces (>30°C)

### 5) Storage

Store in a cool dry place. Storage temperature must not exceed 50°C.

Shelf life is 24 months from date of manufacture under normal storage conditions. Refer to "Lot Number" and "Best Before Date" on can.

## 6) Safety

Please refer to the Material Safety Data Sheet or contact your local 3M™ Toxicology Department.

3M™ 55535 Finish Control Spray is designed FOR PROFESSIONAL INDUSTRIAL USE ONLY.

### 7) Disclaimer

All statements, technical information and recommendations are based on tests we believe to be reliable as at the date of hereof, but the accuracy or completeness thereof is not guaranteed. Please ensure before using the product that it is suitable for your intended use. Since the conditions and methods of use of the product and of the information referred to herein are beyond our control, other than for fraudulent misrepresentation, 3M expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information.



# **Technical Data Sheet**

Effective: 31/07/2019 Supersedes: 07/08/2007

### For Additional Health and Safety Information

3M United Kingdom plc	3M Ireland Limited	3M Denmark a/s
Automotive Aftermarket	Automotive Aftermarket	Automotive Aftermarket
3M Centre,	The Iveagh Building	Hannemanns Allé 53
Cain Road,	The Park	2300 København S
Bracknell,	Carrickmines	
RG12 8HT	Dublin 18	Tel: +45 43480100
Tel: +44 (0)161 237 6391	Tel: +353 12160301	
aadenguiries.uk@mmm.com	aadenquiries.uk@mmm.com	3mkundeservicedk@mmm.com
www.3Mbodyshop.co.uk	www.3Mbodyshop.co.uk	www.3MAuto.dk
3M Finland, Suomen 3M Oy	3M Svenska AB	3M Norge AS
Automotive Aftermarket	Automotive Aftermarket	Automotive Aftermarket
Keilaranta 6	Bileftermarknad	Kanalveien 2
02150 Espoo	19189 Sollentuna	2004 Lillestrøm
Tel: 09 52521	Tel: 08-922100	Tel: 06384
tilaukset@mmm.com	kundservice@mmm.com	kundeservice@mmm.com
www.3M.fi/autotuotteet	www.3M.se/bileftermarkad	www.3m.no/auto
3M Latvija	3M Eesti OU	3M Lietuva
K.Ulmana 5	Pärnu mnt. 158	A.Goštauto str. 40 A
Riga, LV-1004	11317 Tallinn	LT-01112 Vilnius
Tel: +371 67066120	Tel: +372 6 115 902	Tel: +370 5 2160780
www.3m.lv	www.3m.ee	www.3m.lt

© 3M 2019. 3M is a trademark of the 3M company. All rights reserved