TECHNICAL DATA SHEET - MATT CHEM MARINE RANGE

Product: STOPO

Date: 29 September 2008

STOPO AQUAEOUS WATER-REPELLING SATURATOR FOR TEAK AND EXOTIC WOODS

STOPO is a new generation of water-repelling saturator for the treatment of teak and other exotic woods. It is based on an aqueous formula, and does not contain any organic solvents.

STOPO is a colourless water-repellant which reduces significantly the ability of wood to absorb water.

STOPO can be used for both interior and exterior woodwork.

STOPO allows a subsequent application of solvent or aqueous-based paint or varnish.

STOPO comes ready to use and can be applied with a brush on the surface to be treated.

The product starts to work 30 minutes after being applied. According to the climate conditions, the full water-repelling effect is reached 48 hours after being applied. **STOPO** is ready to use. Well shake the bottle before use. Apply with a paint-brush on a clean and dry surface at a temperature > 15°C.

An even better protection can be attained by applying several coats. It is important to wait 30 minutes between coats. The increase in protection diminishes after 2 coats. Each coat uses about 1 litre per 15m².

IMPORTANT: Keep out of reach of children. In the event of contact with eyes/skin, rinse immediately and abundantly with clear water at least 15 minutes. If irritations persist, consult a doctor. Always make beforehand, a test with the surface to be treated to determine the compatibility and the time of contact suited. Store away from freezing.

