

# MATTCO colorless



# TEAK SEALER COLORLESS

## **DESCRIPTION**

**MATTCO** is a colorless sealer for teak.

**MATTCO** contains resins and synthetic polymers.

**MATTCO** prevents mildew and delays the biological degradation of wood by micro-organisms.

MATTCO does not scale, does not yellow and does not crack.

**MATTCO** contains UV protection.

MATTCO nourishes teak and brings back the hot tone of teak.

### **TECHNICAL DATA:**

Physical state : Liquid. Color : White Density : 1008 g/l + /- 10 g/l. Odor : Odorless Chemical Reaction : Neutral. VOC : < 0,2%

### **INSTRUCTIONS OF USE:**

MATTCO is used pur.

Apply to the paint brush on a cleaned, dusted and perfectly dry teak.

Well shake the product before use.

Apply a 1st uniform and regular thin coat in the direction of the wood at an ambiant temperature of minimum 15°C.

Wait 15 minutes and apply a 2nd coat always in the direction of the wood.

Under normal circumstances the teak should be dry to the touch in 30 minutes approximately.

The maximal protection is effective after 12 hours at a room temperature of 20°C (Cool and damp weather slows down

the time of drying)

Indicative coverage: +/- 10 m<sup>2</sup> per litre

**Ref. 350M - Can 1L Ref. 350M.4 - Can 4L** Shelf life : 3 years Keep out of the reach of children. Reclose the packaging after each use.

Exposure to sun and extreme temperatures should be avoided. Keep out of direct sunlight.

Always carry out a test prior to use on the surface to be treated to determine suitability and the appropriate contact time. Before use, read the label safety section for Health and Safety Information or request the safety data sheet to servicetechnique@mattchem.fr.

